



1/14

FIG. 1





3/14

FIG. 3




FIG. 4






FIG. 5



10/511128


5/14

FIG. 6



6/14

FIG. 7



7/14

FIG.8 (a)




FIG.8 (b)





FIG.8 (c)


CORRECTION GAIN K (REPRESENTING K_a , K_b , K_c , AND K_d)



10/511128

8/14

FIG. 9



9/14

FIG. 10

START

INTEGRATE DETECTED VALUE OF GYRO SENSOR TO DETERMINE ESTIMATED BODY POSTURE. USE MOTIONAL ACCELERATION CALCULATED FROM MOTION AT GEOMETRICALLY ESTIMATED BODY POSITION DETERMINED IN PREVIOUS CONTROL CYCLE AND DETECTED VALUE OF ACCELEROMETER TO CORRECT DETECTION DRIFT OF GYRO SENSOR, AND CORRECT DRIFT OF INCLINATION COMPONENT IN ESTIMATED BODY POSTURE. PERFORM YAW CORRECTION, DEPENDING ON SITUATIONS.

S2200

CALCULATE DIFFERENCE BETWEEN VARIATION IN ESTIMATED BODY POSTURE OBSERVED FROM GLOBAL COORDINATE SYSTEM BETWEEN CONTROL CYCLES AND VARIATION IN BODY POSTURE OF DESIRED GAIT OBSERVED FROM GLOBAL COORDINATE SYSTEM (VARIATION IN POSTURE ROTATION ERROR).

S2202

DETERMINE POSTURE ROTATIONAL CENTER

S2204

DETERMINE POSITION/POSTURE BY ROTATING CURRENT ESTIMATED SUPPORTING LEG COORDINATE SYSTEM ABOUT THE POSTURE ROTATIONAL CENTER BY THE DIFFERENCE (VARIATION IN POSTURE ROTATIONAL ERROR) TO OBTAIN UPDATED CURRENT ESTIMATED SUPPORTING LEG COORDINATE SYSTEM.

S2206

S2210

S2208 YES

LANDING
TIME?

DETERMINE NEXT GAIT'S ESTIMATED SUPPORTING LEG COORDINATE SYSTEM SUCH THAT RELATIVE POSITION/POSTURE RELATIONSHIP OF NEXT GAIT'S ESTIMATED SUPPORTING LEG COORDINATE SYSTEM WITH RESPECT TO CURRENT ESTIMATED SUPPORTING LEG COORDINATE SYSTEM IS IDENTICAL TO RELATIVE POSITION/POSTURE RELATIONSHIP OF NEXT GAIT'S SUPPORTING LEG COORDINATE SYSTEM WITH RESPECT TO SUPPORTING LEG COORDINATE SYSTEM IN DESIRED GAIT.

SUBSTITUTE POSITION/POSTURE OF NEXT GAIT'S ESTIMATED SUPPORTING LEG COORDINATE SYSTEM IN POSITION/POSTURE OF CURRENT ESTIMATED SUPPORTING LEG COORDINATE SYSTEM.

S2212

DETERMINE ESTIMATED BODY POSITION ON THE BASIS OF POSITION/POSTURE OF CURRENT ESTIMATED SUPPORTING LEG COORDINATE SYSTEM.

S2214


S2216

CORRECT INERTIAL-NAVIGATION-LIKE BODY POSITION SO THAT DIFFERENCE BETWEEN GEOMETRICALLY ESTIMATED BODY POSITION AND INERTIAL-NAVIGATION-LIKE ESTIMATED BODY POSITION CONVERGES TO ZERO, WHILE DETERMINING INERTIAL-NAVIGATION-LIKE ESTIMATED BODY POSITION/POSTURE ACCORDING TO INERTIAL NAVIGATION BY ACCELEROMETER AND GYRO SENSOR.

RETURN

10/14

FIG. 11



11/14

FIG.12

POSTURE ROTATIONAL ANGLE OF ESTIMATED
SUPPORTING LEG COORDINATE SYSTEM
(VARIATION IN POSTURE ROTATIONAL ERROR)





FIG. 13



13 / 14

FIG.14 (a)






FIG.14 (b)



14/14

FIG. 15

INTEGRATION GAIN K_a FOR
CORRECTING GYRO SENSOR DRIFT



GLOBAL BODY ANGULAR VELOCITY $|\omega_{glz}|$
OBTAINED BY CONVERTING ANGULAR VELOCITY
SENSOR DETECTED VALUE TO GLOBAL
COORDINATE SYSTEM